

## DECLARATION OF PERFORMANCE



Nº: 15-590

1. Unique identification code of the product-type/batch number or other identification element

Impermax 2k
One component waterproofing product
Batch number on each label

Components	Trade name
Primers	Rayston Epoxy 100 / Humidity
	Primer
Waterproofing membrane	Impermax 2k
Finish	Impertrans Pigmented

#### 2. Intended use

Liquid roof waterproofing

#### 3. Manufacturer

Krypton Chemical C/Martí i Franquès, 12 43890, L'Hospitalet de l'Infant (Tarragona, Spain)

#### 4. Systems of assessment of verification of constancy of performance

2

#### 5. Harmonized standard

Non applicable

### 6. In case of the declaration of performance concerning a construction product for which a european technical assessment has been issued

Approval body IETCC issued an ETA-10/0296 based on EAD 030350-00-0402

#### 7. Notified body

Instituto de Ciencias de la Construcción Eduardo Torroja (IETCC)

#### 8. Declared performance

Essential characteristics	Performance
External fire behaviour	Broof(t1): For supports non-combustible and roof slope <20°. Broof(t2): For supports non-combustible for any roof slope NPA. For support combustible
Fire class	E
Use life	W3
Climatic zone	S (Severe)
Use load	P4
Roof slope	S1 to S4
Minimum surface temperature	TL3
Maximum surface temperature	TH4
Hazardous components	Not declared

The performance of the product identified in points 1 and 2 is in conformity with the performance declared in point 8. This Declaration of Performance (DoP) is issued according of Regulation (EU) 305/2011 and under the sole responsibility of the manufacturer identified in point 3.



# DECLARATION OF PERFORMANCE



Nº: 15-590

Signed by Raul Fernandez, Technical Manager on behalf of the manufacturer. L'Hospitalet de l'Infant, September 1st 2015

