



DECLARATION OF PERFORMANCE

Nº: 18-A7B



1. Unique identification code of the product-type/batch number or other identification element

Impermax Cold Polyurea
Two component waterproofing product
Batch number on each label

Components	Trade name
Primers	Rayston Epoxy 100 / Humidity Primer
Reinforcement	Geomax / Rayston Fiber 150
Waterproofing membrane	Impermax Cold Polyurea

2. Intended use

Liquid roof waterproofing

3. Manufacturer

Krypton Chemical
C/Martí i Franquès, 12
43890, L'Hospitalet de l'Infant (Tarragona, Spain)

4. Systems of assessment of verification of constancy of performance

3

5. Harmonized standard

Non applicable

6. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued

Approval body IETCC issued an ETA-17/0509 based on ETAG 005-6:2000. Nº1219

7. Notified body

Instituto de Ciencias de la Construcción Eduardo Torroja (IETCC)

8. Declared performance

Level	1.6 kg/m ²	2 kg/m ²	3 kg/m ²	2 kg/m ² + Rayston Fiber	
External fire	Broof (t1) roof slope < 20° and support A1-A2// NPA for support no A1-A2				
Fire reaction	F				
Use life	W2 (10 years)	W3 (25 years)			
Climatic zone	S (severe)				
Use load	P3: TH2 P2: TH3 P1:TH4	P3: TH2, P3: TH3 P2:TH4	P4: TH2 P3: TH3 P3:TH4	P4: TH2, TH3 P3: TH4 P3: TH4	P4: TH2, TH3 P3: TH4
Roof slope	S1 – S4				
Minimum surface temperature	TL3 (-20°C)				
Maximum surface temperature	TH4 (90°C) / TH3 (80°C) / TH2 (60°C)				



DECLARATION OF PERFORMANCE

Nº: 18-A7B



The performance of the product identified in points 1 and 2 is in conformity with the performance declared in point 8. This Declaration of Performance (DoP) is issued according of Regulation (EU) 305/2011 and under the sole responsibility of the manufacturer identified in point 3.

Signed by Raul Fernandez, Technical Manager on behalf of the manufacturer.

L'Hospitalet de l'Infant, November 31st 2018.

