




DECLARATION OF PERFORMANCE



Nº: 16-59AL

1. Unique identification code of the product-type/batch number or other identification element

Impermax Polyurea H Flex Alum
Bridge deck liquid waterproofing component
Batch number on each label

2. Intended use

Bridge deck liquid waterproofing

3. Manufacturer

Krypton Chemical
C/Marti i Franquès, 12
43890, L'Hospitalet de l'Infant (Tarragona, Spain)

4. Systems of assessment of verification of constancy of performance

2+

5. Harmonized standard

Non applicable

6. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued

Approval body IETCC issued an ETA-16/0149 based on DEE 030350-00-0402.
Nº1219

7. Notified body

Instituto de Ciencias de la Construcción Eduardo Torroja (IETCC)

8. Declared performance

Characteristic	Method	Condition test	Values
Bond strength to support	EN 13596	P1, S0, T5	>1 MPa
Bond strength to support after heat impact		P1, S1, T5	>1 MPa
Tensile stress (initial /heat impact, heat ageing 10mm/min 23°C / 1mm/m - 10°C	EN 527-2, 1B	P1, S0/S1, T5	5 /12
Elongation (initial /heat impact, heat ageing 10mm/min 23°C / 1mm/m - 10°C		P1, S0/S1, T3	15 /15
Resistance to chloride ion penetration	TR 22	P1, S0, T5	Pass (<0,04%)
Resistance to compaction (160°C)	EN 14692 (met 2)	P1, S1.3, T5	Pass
Resistance to perforation (23°C)	TR 006	P1, S0, T5	Pass (I4)
Resistance shear to support/overlay (mastic asphalt (220°C)	EN 13653	P1, S1.2.2, T5	0,4 MPa
Resistance shear to support/overlay (coarse bituminous mixture 160°C)		P1, S1.2.3, T5	0,2 MPa
Watertightness (23°C)	EN 14694	P1, S0, T5	Pass
Bond strength to overlay (220°)	EN 13596	P1, S1.2.2, T5	0,6 MPa



DECLARATION OF PERFORMANCE

Nº: 16-59AL



Bond strength to Coarse bituminous mixture (160°C)		P3, S1.3, T5	0,4 MPa
Resistance to shear to Mastic asphalt (160°C)		P1, S1.2.2, T5	0,25 MPa
High/low service temperature	The effects of low temperature are covered by the capacity to bridge crack		
Resistance to flow	Annex E ETAG 033	P1, S0, T5	Pass
Minimum thickness	2.7 mm		
The effects of climatic conditions on application (Minimum application temperature: 5°C, Maximum application temperature: 40°C)	Annex E ETAG 033	P1, S0, T5	Pass
Bond strength to support			
Bond strength to moisture support	Not relevant the concrete support must have a humidity ≤ 4%		
Bond strength to day joints, (24h, 48h)		P4, S0, T5	>1 MPa
Bond strength to section joints (7d UV)		P4, S0, T5	>1 MPa

The performance of the product identified in points 1 and 2 is in conformity with the performance declared in point 8. This Declaration of Performance (DoP) is issued according of Regulation (EU) 305/2011 and under the sole responsibility of the manufacturer identified in point 3.

Signed by Raul Fernandez, Technical Manager on behalf of the manufacturer.

L'Hospitalet de l'Infant, February 9th 2026


Krypton
Chemical SL
C/ Muri i Pratgat, 12 - Pl. Les Tapes
43000 L'Hospitalet de l'Infant (Barcelona)
Spain
Tel: +34 937 833 977
www.rayston.com

