



DECLARATION OF PERFORMANCE



Nº: 14-570

1. Unique identification code of the product-type/batch number or other identification element

Impermax ST
Solvent-based one component polyurethane aromatic resin
Batch number on each label

2. Intended use

Waterproofing membrane without joints or overlaps, for roofs, cold liquid application

3. Manufacturer

Krypton Chemical
C/Martí i Franquès, 12
43890, L'Hospitalet de l'Infant (Tarragona, Spain)

4. Systems of assessment of verification of constancy of performance

3

5. Harmonized standard

Non applicable

6. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued

ETA 06/0263
DEE 030350-00-0402

7. Notified body

Instituto de Ciencias de la Construcción Eduardo Torroja (IETCC). Nº 1219

8. Declared performance

Essential characteristics	Performance
Outdoor fire behaviour	B _{roof} (t1)
Reaction to fire	F
Life	W3
Climatic zone	S
Usage charge	P4:TH2, TH3
Deck slope	S1-S4
Minimum surface temperature	TL3
Maximum surface temperature	TH4, TH3, TH2
Hazardous substances	Does not contain

The performance of the product identified in points 1 and 2 is in conformity with the performance declared in point 8. This Declaration of Performance (DoP) is issued according of Regulation (EU) 305/2011 and under the sole responsibility of the manufacturer identified in point 3.

Signed by Raul Fernandez, Technical Manager on behalf of the manufacturer.
L'Hospitalet de l'Infant, February 10th 2026.

