

## DECLARATION OF PERFORMANCE



Nº: 19-754

1. Unique identification code of the product-type/batch number or other identification element

Rayston Spray D50 Batch number on each label

2. Intended use

Protection of concrete structures

3. Manufacturer

Krypton Chemical C/Martí i Franquès, 12 43890, L'Hospitalet de l'Infant (Tarragona, Spain)

4. Systems of assessment of verification of constancy of performance

2+

5. Harmonized standard

EN 1504-2:2004

6. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued

Non applicable

7. Notified body

Applus – LGAI Technological Center S.A Certificate of conformity of the factory production control: 0370-CPR-2247

8. Declared performance

Essential characteristics	Performance
Adhesion strength by pull-off test	2.2 MPa
	(EN 1542:1999)
Water vapour permeability	Sd= 9.5 (Class II)
	(EN ISO 7783:2012)
Liquid water permeability	0.0008 kg/m2 h <sup>0.5</sup> (compliant)
	(EN 1062-3:2008)

The performance of the product identified in points 1 and 2 is in conformity with the performance declared in point 8. This Declaration of Performance (DoP) is issued according of Regulation (EU) 305/2011 and under the sole responsibility of the manufacturer identified in point 3.

Signed by Raul Fernandez, Technical Manager on behalf of the manufacturer. L'Hospitalet de l'Infant, December 4th 2019.

