




# DECLARATION OF PERFORMANCE



Nº: 14-591

## 1. Unique identification code of the product-type/batch number or other identification element

Impermax Polyurea H  
Two component waterproofing product  
Batch number on each label

Components	Trade name
Primers	Rayston Epoxy 100 / Humidity Primer
Waterproofing membrane	Impermax Polyurea H
Finish	Impertrans

## 2. Intended use

Liquid roof waterproofing

## 3. Manufacturer

Krypton Chemical  
C/Martí i Franquès, 12  
43890, L'Hospitalet de l'Infant (Tarragona, Spain)

## 4. Systems of assessment of verification of constancy of performance

3

## 5. Harmonized standard

Non applicable

## 6. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued

ETA-06/0263  
DEE 030350-00-0402

## 7. Notified body


Instituto de Ciencias de la Construcción Eduardo Torroja (IETCC). Nº1219

## 8. Declared performance

Essential characteristics	Performance
External fire behaviour	B <sub>roof</sub>
Fire class	F
Use life	W2
Climatic zone	S (Severe)
Use load	P4
Roof slope	S1 to S4
Minimum surface temperature	TL3
Maximum surface temperature	TH4
Hazardous components	Not declared

The performance of the product identified in points 1 and 2 is in conformity with the performance declared in point 8. This Declaration of Performance (DoP) is issued according of Regulation (EU) 305/2011 and under the sole responsibility of the manufacturer identified in point 3.

Signed by Raul Fernandez, Technical Manager on behalf of the manufacturer.  
L'Hospitalet de l'Infant, February 10<sup>th</sup> 2026

  
Raul Fernandez  
Krypton Chemical SL  
D-43000 Tarragona  
Ctra. de Tarragona, 12  
Edificio 10  
08800 L'Hospitalet de l'Infant  
Tel: +34 93 455 00 00  
Fax: +34 93 455 00 01