



DECLARATION OF PERFORMANCE

Nº: 19-595



1. Unique identification code of the product-type/batch number or other identification element

Impermax Polyurea H Supreme
Batch number on each label

2. Intended use

Protection of concrete structures

3. Manufacturer

Krypton Chemical
C/Martí i Franquès, 12
43890, L'Hospitalet de l'Infant (Tarragona, Spain)

4. Systems of assessment of verification of constancy of performance

2+

5. Harmonized standard

EN-1504-2:2004

6. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued

Non applicable

7. Notified body

Applus – LGAI Technological Center S.A
Certificate of conformity of the factory production control: 0370-CPR-2247
Certificate date: 05/11/2019

8. Declared performance

Essential characteristics	Performance
Adhesion strength by pull-off test	0.9 MPa (EN1542:1999)
Water vapour permeability	Sd=1.0 (Class I) (EN ISO 7783:2012)
Liquid water permeability	0.02 kg/m ² h ^{0.5} (compliant) (EN 1062-3:2008)

The performance of the product identified in points 1 and 2 is in conformity with the performance declared in point 8. This Declaration of Performance (DoP) is issued according of Regulation (EU) 305/2011 and under the sole responsibility of the manufacturer identified in point 3.

Signed by Raul Fernandez, Technical Manager on behalf of the manufacturer.
L'Hospitalet de l'Infant, December 4th 2019

